

HATHORN H2

CAMERA SYSTEM



Get A Quote

PROUDLY DESIGNED AND MANUFACTURED IN NORTH AMERICA



Self-Leveling
Camera Heads



Works with 18V
Milwaukee® or
Equivalent
Batteries



200 ft of
Push Rod



512Hz High
Power Sonde



Industry-Leading
Warranty

The Hathorn® H2 comes with a 7" shatter-resistant LCD monitor, 200 ft. of premium push rod and your choice of straight-view or self-leveling camera heads, all with cool running, super-bright LED lights. The H2 also includes an on-screen footage counter in feet and meters, as well as a 512Hz high power sonde control.

Being aimed at the budget conscious user who wants a robust, easy-to-use system, without paying for extra options, the H2 camera system does not have a recording option. The H2 is an entry level inspection camera offering the same rugged quality and portability of our more expensive models. All Hathorn products are compatible with 18V Milwaukee® batteries offering the H2 over 6 hours of runtime on a single charge.

Trusted by plumbers and contractors to deliver rugged dependability and portability. Designed and manufactured in North America, with a full one-year warranty.



Ditchwitchwest.com



PROUDLY DESIGNED AND MANUFACTURED IN NORTH AMERICA

HATHORN H2

CAMERA SYSTEM



Specifications

Display

| | |
|-------------------------|------------------------------------|
| Size & Type | 7" (17.8cm) impact-resistant LCD |
| Resolution & Brightness | 1024 x 600 pixels with 1,000 cd/m2 |

Recording, Storage & Features

| | |
|-------------------|---|
| Footage Counter | Feet or meters - resettable |
| Sonde Frequencies | High power 512Hz |
| Push Rod | 200 ft. of HDPE push rod with coax core |

Power

| | |
|---------------------|---------------------------------------|
| Battery (not incl.) | Only Milwaukee® M18 18V or equivalent |
| Battery Life | ~6Hrs. using 3.0Ah |
| AC/DC Adapter | 12V - 4.1A (included) |

Weight & Dimensions

| | |
|------------------------|--|
| Weight without Battery | 45lb (20.4Kg) |
| Dimensions (L x W x H) | 19" x 15.5" x 29.5" (48cm x 39cm x 75cm) |

Environmental

| | |
|-----------------------|-------------------------------|
| Water Resistance | IP65 when the lid is closed |
| Operating Temperature | 14°F to 122°F (-10°C to 50°C) |
| Storage Temperature | -4°F to 140°F (-20°C to 60°C) |

| Catalog # | Camera Head | Self Levelling | Rod Length | Rod Size | Min. 90° Elbow | Max Pipe Well Lit |
|------------|-------------|----------------|------------|----------|----------------|-------------------|
| H2-2168-SL | 1.68" | ✓ | 200 ft | 1/2" | 3" | 12" |
| H2-2143-SL | 1.43" | ✓ | 200 ft | 1/2" | 3" | 10" |
| H2-2123-SL | 1.23" | ✓ | 200 ft | 0.400" | 2" | 6" |
| H2-2100 | 1" | ✗ | 200 ft | 3/8" | 1.5" | 4" |



Ditchwitchwest.com

